

Watheroo Dolomitic Lime

ABN 29 498 013 357

PO Box 71 Two Rocks WA 6037

Peter & Terri Manns

0428 922 340 & 0418 922 340

www.dolomite.com.au



LIME WA INC.

Code of Practice

Accredited

Lime Suppliers



Product Information Sheet



Approved Laboratories



GENERAL INFORMATION

Pit Name	Watheroo Dolomitic Lime	Date of Analysis	February 8th 2013
Location	Watheroo	Laboratory No.	12A0278-001
Product Description	Dolomitic Lime	Product Screened	Yes
Weigh System ***	Compuload Loader Scales	Screen Size (mm)	2.00 mm
*** This supplier uses an accredited weigh system verified by the Department of Consumer Protection			

CODE OF PRACTICE APPROVED LABORATORY TEST REPORT

	THIS SAMPLE	RANGE FOR PIT	THIS SAMPLE	RANGE FOR PIT
Sieve Range (mm)	% Weight		% Neutralising Value	
0.000 – 0.125	30.7	34.2 - 44.7	96.5	96.5 - 99.6
0.125 – 0.250	12.9	9.1 - 12.9	88.2	82.9 - 91.1
0.250 – 0.500	13.8	10.7 - 13.8	92.9	83.7 - 94.1
0.500 – 1.000	14.3	12.5 - 14.9	95.9	87.6 - 95.9
> 1.000	28.0	20.6 - 29.9	98.7	89.8 - 98.7
Weighted Average NV			95.1	90.8 - 95.5
Bulk NV	95.2	91.6 - 95.2		
Calcium (Ca) (1 M HCl)	18.6	18.0 - 21.0		
Magnesium (Mg) (1 M HCl)	11.1	10.0 - 11.8		
Sodium (Na) (1 M HCl)	0.1	0.1		

Statement by Supplier : The above analysis, provided by a Code of Practice approved laboratory, is a true representation of the product being supplied from the nominated pit. Pit ranges have been calculated from the last 5 samples analysed.

Date : Name : Signature :

Disclaimer : Lime WA Inc. requires members to provide the above details in accordance with the industry Code of Practice requirements but makes no claims and provides no guarantees on the quality or suitability of the product supplied. Product supplied by Lime WA Inc. members occurs naturally and has a moisture retention capacity that varies according to seasonal conditions. As this cannot be controlled by suppliers, moisture level analyses are not included on this information sheet. Lime WA Inc. is not responsible for any claims and/or liabilities arising from the supply and/or use of the product supplied. However, users are invited to contact the Association on 0419 575 737 in the event of any dissatisfaction with the product description provided by accredited lime suppliers.